



JLD International BV

Boomkorstraat 5
1446 AK PURMEREND
The Netherlands

Tel. +31 (0)299 622 396


Mail. info@JLDinternational.com
Web. www.JLDinternational.com

*Safety, quality and the environment are paramount at JLD. We are: VCA** | ISO 9001 | CO2 Level5 certified. More information about this can be found on our website: www.JLDinternational.com*

VINYL SHEETPILE PROFILE JLD Z 300/5,5

Type JLD Z	300/5,5	[imperial]
Material	VINYL	
Section Width = w	11,8	in
Section Height = h	4,53	in
Section Thickness = t	0,22	in
Section Modulus	5,95	in ³ /ft
Moment of Inertia	13,49	in ⁴ /ft
Allowable Moment	1,6	ft-kips/ft
Ultimate Moment	3,2	ft-kips/ft
EI Stiffness	--	ibf-in ² x10 ⁶ /ft
EI MAX Stiffness	--	ibf-in ² x10 ⁶ /ft
Weight	2,89	lb/ft ¹
Weight	2,93	lb/ft ²


Accessoires	C270/300	C300	C120	[imp]
Width = w	2,2	1,8	5	in
Height= h	2,2	0,61	2,4	in
Thickness = t	--	--	0,6	in
Weighth	1,06	1,06	0,77	lb/ft



Corner C270/300




Corner C300



Cap C120

ACCESSOIRES

Corner C270/300; Corner C300; Cap C120



Type Z 300/5,5

